

FERRI®

DKI 800



MOWING DISK FOR FRONT MOUNTING


For tractors with front linkage and pto



Floating system: it allows the mowing disk to automatically adapt to the ground without the intervention of the operator. Excellent productivity and the cut of grass even.

Technical data

Model	Mowing disk diameter	Weight	Tractor HP	Min. Tractor width	Min. Tractor weight
	cm	Kg	HP	m	Kg
DKI	80	800	80÷110	2,10	2.800



Mowing disk in wear resistant material



Automatic deviation and return device



Self ventilated knives



Tap for the hydraulic block during the transport



Floating system for self-levelling to the ground



Anti-projectile protections in resistant material



Features:

- Mowing disk diameter 80 cm in wear resistant material with automatic deviation and return device simultaneously with the advancement of the tractor.
- Self ventilated knives
- Continuous cutting grass and shrubs in the presence of guard rails, traffics signs and other obstacles.
- Support plate
- Abrasion resistant guard
- Floating system: it allows the mowing disk to automatically adapt to the ground without the intervention of the operator.
- Excellent productivity and the cut of grass even.
- Front mounting (tractor must be equipped of front pto) Independent hydraulic system with high-pressure pump and motor
- Oil cooler with radiating mass in high strength aluminium
- Hydraulic shock absorber
- Bumpers with illumination system
- Electro-hydraulic control box with manipulators in tractor cab



FERRI®

FERRI srl
Via Govoni, 30
44034 Tamara (FE) Italy
Tel. +39 0532 866866
Fax +39 0532 866851
info@ferrisrl.it - www.ferrisrl.it

Spare parts:
Tel: +39 0532 866866
Fax: +39 0532 867050
e-mail: parts@ferrisrl.it

After Sales Service
Tel: +39 0532 866991
Fax: +39 0532 866851
e-mail: service@ferrisrl.it